



BATHROOMS UNLIMITED SERVICES Ltd.

**SPECIALIZING IN COMPLETE
KITCHEN & BATHROOM REMODELING**

Visit Our Showroom 14616 - 111 Avenue
LICENSED, INSURED | (780) 489-5168 | BONDED, BBB MEMBER

"Serving Edmonton and Surrounding Area Since 1987"

Washupito's Tiendita

SANITOP

[Call for Pricing](#)



The smallest and quietest macerator on the market !

The Sanitop is a system that is used to install a complete bathroom up to 12 feet below the sewer line, or even up to 120 feet away from a soil stack. It can handle the effluent from a toilet and sink. A normal operating cycle for Sanitop takes about 10 - 15 seconds depending upon the discharge pipe run configuration; power consumption is therefore minimal. A non-return valve, which comes already assembled on the discharge elbow, prevents back flow into the unit.

The design of this model consists of vibration absorbers which enable the reduction of operating sound by reducing the transmitted sounds from any location where such resonance transmission could occur. This new design reduces the operating sound of this pump by 10dB.

The Sanitop is simplicity itself to install; there are just five connections.

- The macerator/pump is connected to the spigot of a horizontal rear discharge toilet.
- The toilet tank is connected to the water supply.
- The macerator/pump is connected to the small diameter discharge pipe work (3/4" or 1") PVC/CPVC or copper.
- The macerator/pump is connected to an existing vent system in the building.
- The macerator/pump is connected to the electrical supply.

The Sanitop unit must be connected to our rear discharge toilet(either round or elongated). This system uses 1.6 USG (6 liters) of water per flush.

Note:

This toilet only works in combination with the Sanitop. The Sanitop has been certified to American and Canadian Standards (UPC & CSA).



Motor RPM	3600
Horsepower	0.3
Electrical Supply	115 V / 60 Hz
Flow rate at max head USG/MIN	12 ft : 14 gal/min; 3 ft : 2min
Amperage (Consumption)"	5.0
Discharge Pipe Diameter	3.4"
Vertical Discharge	12 ft
Horizontal Discharge	120 ft
Maximum Temperature	104°F
Water Consumption	1.6 US gal
Dimensions (measured from floor level)	H 107.16" x W 13" x D 61.2"
Materials	Polypropylene, C.R.P., Stainless Steel, Neopren

[Vendor Information](#)