



BATHROOMS UNLIMITED SERVICES Ltd.

**SPECIALIZING IN COMPLETE
KITCHEN & BATHROOM REMODELING**

Visit Our Showroom 14616 - 111 Avenue

LICENSED, INSURED | (780) 489-5168 | BONDED, BBB MEMBER

"Serving Edmonton and Surrounding Area Since 1987"

Washupito's Tiendita

SANISTAR

[Call for Pricing](#)



This modern shaped self-contained china toilet emulates the European wall-hung toilets that are so popular as of late. The Sanistar can be used with a hand basin only. The wastewater of a hand basin drains into the toilet motor and after a certain amount of water has entered, the motor will start and pump away the wastewater. At the same time it will also partially empty the bowl, which after the motor stops, will be refilled with clean water.

The Sanistar saves space and can be hung on any sturdy wall. It comes complete with a wall bracket system that can be placed against a wall or if you start from scratch-it can be built into the wall and mounted against 2" x 6" studs. The wall bracket has feet that can be adjusted to allow the Sanistar to be hung at a height that is comfortable for the user, for example between 15 and 18 inches. The Sanistar uses a minimum amount of water. The flushing mechanism is electrically timed to allow approximately 4 litres (1.1 USG) of water to pass through the toilet.

The Sanistar has no external water tank as the flushing mechanism is built in and is totally electric. After use, one presses a pneumatic button on top of the bowl, this activates a timer and a solenoid valve in order to fill and wash the sides of the bowl. The motor starts and the waste and paper are sucked inside, where it is macerated and pumped away. The motor stops after approximately 15 seconds and the timer programs the refill of the bowl with fresh water.

The discharge pipe of the Sanistar is 1 inch in diameter; the pump operates at 7 PSI and pumps the effluent

upwards to 9 feet and/or 100 feet horizontally. The discharge pipe-work may be made with either copper or solvent welded plastic material, provided that a consistent gravity fall is maintained throughout the run. The Sanistar also allows for a hand basin hookup.

The Sanistar is a self contained toilet with the macerator pump and an electrical activated flushing action built inside the unit. The Sanistar does not depend on gravity, therefore it can be used where large diameter pipe cannot be used.



Motor RPM	3600
Horsepower	0.4
Electrical Supply	110-115V; 60Hz;
Flow rate at max head USG/MIN	9 ft:18 usg/min;3 ft:25 usg
Amperage (Consumption)"	9.0 AMP
Discharge Pipe Diameter	1" diameter
Vertical Discharge	9 ft
Horizontal Discharge	100 ft
Gravity fall on horizontal installations	1/4" per ft
Normal Running Time WC	10-15 seconds
Maximum Temperature	95°F
Water Consumption	1.3 US gal
Dimensions (measured from floor level)	H16-3/8" x W15 3/4" x D20 1/2"
Materials	Polypropylene, C.R.P., stainless steel, Neoprene

[Vendor Information](#)